



# vP1,2B

## Technical Specs sheet

500 x 500 mm

BROMPTON R2 RECEIVINGCARD  
 COLOR MATCHING TOOL  
 1-6° CONCAVE  
 HIGH-LEVEL  
 BLACK-FACE  
 QUICK-LOCK-SYSTEM  
 MAGNETIC FAST-RIGG  
 FAST REPLACEABLE BACKBOX



<b>Pixelpitch</b>	1,25 mm
<b>Brightness</b>	800 nit
<b>Weight</b>	9,8 kg
<b>Power Consumption</b>	Nominal 44 W   max. 130 W
<b>SMD-Type</b>	Nationstar LIGBF1010
<b>SMD Specifications</b>	Black-Face, High-Level
<b>Color Depth</b>	16 Bit
<b>Resolution</b>	400 x 400 px
<b>LED Driver</b>	MBI5264
<b>Receivingcard</b>	Brompton R2+
<b>Scanmode</b>	1/25
<b>Refreshrate</b>	≥ 3.840 Hz
<b>Horiz. Angle of View</b>	+85° / -85°
<b>Vert. Angle of View</b>	+85° / -85°
<b>Contrast</b>	> 5.000:1
<b>Voltage Range</b>	AC 88-264V / 50-60 Hz
<b>Connection</b>	Neutrik PowerCON TRUE1
<b>Dimensions (WxHxD)</b>	500 x 500 mm   T= 80 mm
<b>IP Rating</b>	IP40
<b>Temperature Rating</b>	-30°C bis +45°C (In Operation) -10°C bis +55°C (Stored)
<b>Producthighlights</b>	1-6° Concave Installation, Color Matching Tool, Magnetic Fast-Rigg, Fast Replacable Backbox
<b>Certification</b>	