

# eT4io

## Technisches Datenblatt

1.000 x 500 mm

ICND2153S DRIVER IC  
7.680HZ REFRESHRATE  
FAST REPLACEABLE BACKBOX  
MAGNETIC FAST-RIGG



|                            |                                                                                |
|----------------------------|--------------------------------------------------------------------------------|
| <b>Pixelpitch</b>          | 4,63 mm                                                                        |
| <b>Helligkeit</b>          | ≥ 7.000 nits                                                                   |
| <b>Gewicht</b>             | 11,6 kg                                                                        |
| <b>Nennleistung</b>        | Typisch 105 W   max. 336 W                                                     |
| <b>LED-Typ</b>             | SMD 1921                                                                       |
| <b>LED Merkmale</b>        | Matt-Face, High-Level                                                          |
| <b>Farbtiefe</b>           | Bis zu 16 Bit                                                                  |
| <b>Auflösung</b>           | 216 x 108 px                                                                   |
| <b>LED Treiberchip</b>     | ICND2153S                                                                      |
| <b>Receivingcard</b>       | Novastar A10S Pro                                                              |
| <b>Scantyp</b>             | 1/6                                                                            |
| <b>Refreshrate</b>         | ≥ 7.680 Hz                                                                     |
| <b>Horiz. Blickwinkel</b>  | +150°   -150°                                                                  |
| <b>Vert. Blickwinkel</b>   | +140°   -140°                                                                  |
| <b>Kontrast</b>            | > 3.600:1                                                                      |
| <b>Spannungsbereich</b>    | AC 88-264V   50-60 Hz                                                          |
| <b>Stromanschluss</b>      | Seetronic TR1                                                                  |
| <b>Abmessungen (BxHxT)</b> | 1.000 x 500 x 88 mm                                                            |
| <b>IP Klasse</b>           | IP 65 Front   IP54 Back                                                        |
| <b>Temperaturbereich</b>   | -30°C bis +45°C (Im Betrieb)<br>-10°C bis +55°C (Lagernd)                      |
| <b>Produkthighlights</b>   | Optimales Preis-Leistungs-Verhältnis,<br>7.680 Hz Refreshrate, Hohe Helligkeit |

### Zertifizierungen



Stand: 04/2025